

NT3

Studio and Location Multi-Powered 3/4" Condenser Microphone

AUSTRALIA
107 Carnarvon st, Silverwater NSW 2128 Australia
Ph: +61 2 9648 5855 Fx: +61 2 9648 2455

USA
PO Box 91028, Long Beach CA 90809-1028
Ph: +1 562 364 7400 Fax: +1 888 412 4664



Features

- True condenser externally biased 3/4" capsule
- Dual power operation
- Cast metal body with durable satin-nickel finish
- Transformerless output
- Internal capsule shock mounting
- High level of RF rejection
- Audio-grade surface mount components
- Full frequency response
- Designed and manufactured in Australia
- Free 10 year extended warranty when you register online at www.rodemic.com/warranty

Specifications


Acoustic Principle	Pressure gradient
Directional Pattern	Cardioid
Frequency Range	20 Hz-20 kHz
Sensitivity	-39 dB re 1 Volt/Pascal (12 mV @ 94 dB SPL) +/- 2 dB @ 1kHz
Output Impedance	200Ω
Dimensions	Length - 206mm (8.1102") Diameter - 32mm (1.2598")
Output Connection	3 pin XLR, balanced output between Pin 2 (+), Pin 3 (-) and Pin 1 (ground)
Shipping Weight	640g
Net Weight	371g

Incl. Accessories

- RM3 stand mount
- ZP1 zip pouch
- WS3 windshield



Polar Pattern



Frequency Response

